

# CS Hyde Company

1351 N. Milwaukee Ave.,  
Lake Villa, IL 60046  
Ph. 847-395-0325 Fax 847-395-0334  
[sales@cshyde.com](mailto:sales@cshyde.com) / [www.cshyde.com](http://www.cshyde.com)

## PRODUCT INFORMATION

### **17-FibG-DS** **Glass Cloth Tape w/ Silicone** **Adhesive 2 sides**

#### **PRODUCT DESCRIPTION**

This product is a glass cloth tape with an aggressive silicone adhesive on both sides.

#### **APPLICATION INFORMATION**

This tape is designed for high temperature plasma and flame spray masking. The use of an overlay when grit blasting may be needed. The overlap end is designed not to lift at high velocity grit blasting or thermal spray.

## **TECHNICAL DATA**

<b><u>PROPERTY</u></b>	<b><u>TEST METHOD</u></b>	<b><u>DATA</u></b>
Backing Thickness		.004
Backing Material		Glass Cloth
Adhesive System		Silicone
Adhesive Thickness (in.)		.003
Adhesion (oz/in.)	ASTM - D 1000	30
Tensile Strength (psi)	ASTM - D 3759	175
Max. Operating Temp. (F)		500
Rolls-Royce Aero Repair	CSS13	Approved

\*The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.